


Modify History

No.	Date	Version	Modify Content
1	2006.08.02	V1.0	Release the PS Schematic of GSM7702.
2	2006.09.26	V2.0	Change the BAT101 to 1105 0000 0003.
3	2006.09.26	V2.0	Add TP401(PWON).
4	2006.09.26	V2.0	Delete R109(0ohm),Add R123,R124(0ohm).
5	2006.09.26	V2.0	Change the Keypad Backlights from serial to parallel,add C423.
6	2006.09.26	V2.0	Delete all the testpoints except the technologic testpoints.
7	2006.09.26	V2.0	Change CN202(Camera Connector) to ELCO(1.5mm height).
8	2006.09.26	V2.0	Add L323,C319,C324,C325,deleteR303,R306,L306,L322 for RF antenna matching.
9	2006.09.26	V2.0	Add C239(22pF) for LCD_RST EMI.
10	2006.09.26	V2.0	The part of preventing VRSIM leakage current in FTA is NF.
11	2006.09.26	V2.0	Change R302 from 18ohm to 27ohm.
12	2006.11.06	V3.0	Add BAT102(VA5) as the substitution of BAT101(VB3).
13	2006.11.06	V3.0	Delete 22uF C149.
14	2006.11.06	V3.0	Change R317 to NF.
15	2006.11.06	V3.0	Add 22pF C424, C425 for EMI.
16	2006.11.06	V3.0	Add R240 to prevent the leakage current from V_CH to VBUS.
17	2006.11.20	V3.1	Delete R121, add C149 for detremble circuit.
18	2007.01.18	V3.2	Change BAT102 from VA5 to 2901 0400 0023
19	2007.01.18	V3.2	Change R238 from NF to 47K
20			
21			
22			
23			
24			
25			
26			
27			
28			
29			
30			
31			
32			

BLOCK DIAGRAM



AMOI

Amoi Electronics Co., Ltd.

Title GSM7702

Size A3 Sheet Name BLOCK DIAGRAM Rev V3.2

ENGINEER: Name

Date: Thursday, January 18, 2007 **Sheet** 0 of 5

